

XLED home 1 SL

The ideal team player.

Now 25% more light for the same amount of electricity.

The XLED home 1 SL LED floodlight stays cool. It emits only a fraction of the heat conventional halogen floodlights do which means it can also be installed without an issue under porches. And STEINEL's patented Active Thermo Control cooling system additionally protects the floodlight from overheating. Whether interconnected or used on its own in conjunction with a sensor, the powerful floodlight makes your property as bright as day; since the economical 12 W LEDs replace 150 W of halogen light and bathe an area of 150 sq.m. in light that's as bright as day. Cool stuff.

LED
30 years
(Ø 4.5 h/day)

12w
920lm
76,6lm/W

6700 K
cold-white

IP 44


180° horizontal
120° vertical

networkable

energy saving

5 JAHRE GARANTIE
functional warranty

EAN XLED home 1 SL white	4007841 659813
EAN XLED home 1 SL silver	4007841 659714
EAN XLED home 1 SL black	4007841 659912
Dimensions (h x w x d)	175 x 210 x 180 mm
Power supply	230-240 V, 50 Hz
Output	12 W
Brightness	920 lm
Efficiency	76.6 lm/W
Colour temperature	6700K/SDCM 6
Colour rendering	Ra ≥ 80
LED life expectancy	50,000 h (L70B10 to LM80)
LED cooling system	Active- and Passive Thermo Control
Floodlight swivelling range	180°
Floodlight tilting range	120°
IP rating	IP 44
Protection class	I
Material	UV-resistant plastic with aluminium heat sink
Temperature range	-20 to +40°C
With lamp	STEINEL LED system



Including STEINEL LED system



Intelligent LED cooling system



UV-resistant plastic

